



NITRASIL

NITRASIL engineering ceramics have been specially developed for use in industries requiring a strong and durable material that can be used at high temperatures, while remaining chemically inert.

Product Description

NITRASIL ceramic material consists of a high strength, durable silicon nitride which yields superior thermal insulation and electrical insulation properties. Moreover, the NITRASIL material grade is not affected by induction currents.

NITRASIL engineering ceramic products find application in extreme conditions. NITRASIL is commonly used as a high temperature insulation material and can be used in applications up to 1,400 degrees C. Applications examples include:

Product Advantages

- Excellent resistance to oxidation is achieved up to 1150°C.
 - Resistant to almost all chemicals and non-ferrous molten metals.
 - Excellent Thermal Insulation
 - Excellent Electrical Insulation
 - High Strength
 - High Durability
 - Suitable for Applications up to 1400°C.
 - Minimal Molten Metal Wetting
 - Lightweight
 - Resistant to Thermal Shock
 - Resistant to Thermal Cycling
 - Resistant to Industrial Chemicals
-

Approved Applications

- Thermocouple sheaths
- Molten aluminium handling
- Molten steel handling

Physical Properties

Property	Unit	Value
Compressive strength	MPa @ 20°C	550
Fracture toughness	MPa. m ^{1/2}	3
Hardness Hv		1100
Flexural strength at ambient	Mpa @ 20°C	190
Density	g / cm ³	2.4
Poissons ratio		0.27
Electrical resistivity	Ωcm	>1010
Thermal expansion	10 ⁻⁶ / °C	3
Thermal conductivity	W/mK	16
Maximum intermittent operating temperature	°C	1400
Maximum continuous operating temperature	°C	1150

Storage

- Store in a cool dry place
- Take care not to exceed safe working loads and heights for storage shelves and racks



NITRASIL

ARCLEX

FEROFORM

FIREFLY

NITRASIL

REFEL

**REFRACTORY
PRODUCTS**

REFRAVER

Tenmat Wear Ltd
Northbanks Industrial Park
Frank Perkins Way, Irlam
Manchester
M44 5EW United Kingdom

htsales@diamorph.com
UK: +44 161 4702689
USA: +1 302-6884990
Czech Republic: +420 378 010 910

tenmatwear.com



Advanced materials.
tenmatwear.com

Tenmat Wear warrants the materials it produces will conform to Tenmat Wear specifications and approved drawings where applicable. It is entirely the customer's responsibility to make the final product choice and satisfy themselves of the suitability of the product for the intended application, carrying out testing where required. For construction projects, all products which the customer is intending to use on a particular project must be approved in writing by the customer's building designer, system designer or design control professional, to ensure compliance with the latest regulations.

The information contained in Tenmat Wear data sheets is presented in good faith. The values are "typical only" and are based on test results generally in accordance with BS2782, ASTM, a variety of other main test bodies along with Tenmat Wear internal test methods. These values should not be relied upon for specification purposes or the primary selection of materials. As the data sheet values are typical only, Tenmat Wear does not warrant the conformity of its materials to these properties or the suitability of its materials for any particular purpose. It is the responsibility of the customer to do the necessary testing and satisfy themselves the product is suitable for the intended application.

